

Model: B2M



## MIDI Implementation Chart

Version: 1.0

Function...		Transmitted	Recognised	Remarks
<b>Basic Channel</b>	Default	1	X	
	Changed	1	X	
<b>Mode</b>	Default	Mode 4	X	
	Messages	X	X	
	Altered	X	X	
<b>Note Number</b>		21-76	X	
	True voice	X	X	
<b>Velocity</b>	Note On	O	X	
	Note Off	X	X	
<b>After Touch</b>	Key's	X	X	
	Channel	X	X	
<b>Pitch Bend</b>		O	X	14-bit ±2 semitone range
<b>Control Change</b>	0-127	123 (All Notes Off)	X	Transmitted at power-on only
<b>Program Change</b>	True Number	X	X	
<b>System Exclusive</b>		X	X	
<b>System Common</b>	Song Position	X	X	
	Song Select	X	X	
	Tune Request	X	X	
<b>System Real Time</b>	Clock	X	X	
	Commands	X	X	
<b>Aux Messages</b>	Local On/Off	X	X	
	All Notes Off	X	X	
	Active Sensing	X	X	
	System Reset	X	X	
<b>Notes</b>	The unit does not receive MIDI, it is only a transmitter.			

Mode1: Omni On, Poly  
Mode3: Omni Off Poly

Mode2: Omni On, Mono  
Mode4: Omni Off, Mono

O:Yes  
X: No

[www.sonusus.com](http://www.sonusus.com) — for the latest information and details on other **SONUUS** products visit our web site.

**SONUUS, B2M** are Trademarks or Registered Trademarks of Sonuus Limited.

The information contained herein is subject to change without notice.